

PRO 10% IAT

➤ DESCRIPTION

Anti-freeze for direct application, formulated with ethylene glycol and a mixture of inorganic technology (IAT) corrosion-inhibitors, as well as anti-cavitation, anti-lime and anti-foam additives, designed to protect the various metals in latest generation internal combustion engine cooling circuits, including the aluminium and light alloys, thereby providing efficient protection for the engine, radiator, water pump and heavy cooling circuit.

PROQUISUR does not recommend mixing this product with other coolants since this can reduce quality.

➤ PHYSICAL AND CHEMICAL PROPERTIES

ASPECT	LIQUID
COLOUR	FLUORESCENT GREEN, PINK, YELLOW OR BLUE
ODOR	CHARACTERISTIC
pH at 20°C	7,5 - 9,5
DENSITY at 20°C	1,040 +/- 1.050 g/cm3
SOLUBILITY IN WATER	100% SOLUBLE
FLASH POINT	NOT APPLICABLE
FREEZING POINT	-5°C +/- 1 °C
BOILING POINT	+109°C

➤ SPECIFICATIONS

UNE 26.361.88

➤ USE

Suitable for all vehicle types and makes.
Indicated for all types of cooling systems.

➤ PRESENTATION

Available packaging 1L, 4L, 5L, 20L, 60L, 200L y 1000L.